



# Enviro Prime GT1

## Solvent Free Primer



### DESCRIPTION

Enviro Prime GT1 is a non-porous, solvent free primer, specifically formulated to be used with Enviro GTX to improve bonding, when adhering to Enviro HP1200.

### FEATURES

- Solvent Free
- Internal and External Priming
- Excellent Water Resistance
- Non-Flammable
- Fast Drying

### TYPICAL USES

Enviro Prime GT1 can be used as a primer for Enviro GTX, when direct stick tiling over Enviro HP1200. Enviro Prime GT1 can be used internally and externally, in the following areas:

- Rooftops
- Stairways
- Balconies

### PHYSICAL PROPERTIES

Appearance	Blue Paste
Dry Time	20 – 40 minutes

### SUBSTRATE PREPARATION

Ensure the surface of Enviro HP1200 is clean, dry and free from any loose particles and surface residues.

For further information on substrate preparation or for project specific advice, please consult EnviroSystems.

[customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

### MIXING

Stir well before use, do not dilute.

### APPLICATION

Enviro Prime GT1 can be applied to a prepared substrate, using a brush or roller, to achieve a minimum dry film thickness (DFT) of 0.1 mm.

Enviro Prime GT1 must only be applied when the surface temperature is between 10°C and 35°C.

### COVERAGE

The consumption of Enviro Prime GT1 will depend on weather, substrate conditions and application techniques.

Typical coverage rate is: 10m<sup>2</sup>/ L

### PACKAGING & COLOURS

Enviro Prime GT1 is supplied in 4 litre pails.

### CLEANING

Excess Enviro Prime GT1 can be cleaned using a damp cloth. Tools can be cleaned up with water prior to curing. Cured material must be mechanically removed.



## SHELF LIFE

Enviro Prime GT1 can be stored in its original sealed containers for up to 12 months in controlled environments. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.

## HEALTH & SAFETY ADVICE

Enviro Prime GT1 contents are considered non-flammable. Always provide adequate ventilation and wear appropriate Personal Protection Equipment (PPE) during use. Avoid breathing vapours. Avoid contact with skin. If swallowed, DO NOT induce vomiting, give glass of water and seek immediate medical advice. If contact with skin, wash off splashes of material with clean water and soap. If irritation occurs seek immediate medical advice. Refer to MSDS.

**NOTE:** Safety Data Sheets are available upon request by emailing [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

## We're here to help you!

It is a good idea to keep a journal of your waterproofing job, whether big or small.

- Take pictures at all stages of your work, including preparation
- Record the quantity and description of products used with corresponding batch numbers
- Record dates and times of when you applied products, from start to finish

Please do not hesitate to contact us for any questions you may have.

EnviroSystems Technologies Pty Ltd

**Address** 295 Princes Highway, St Peters NSW 2044  
Sydney, Australia  
**Phone** +61 2 8595 8699  
**Fax** +61 2 8595 8660  
**Email** [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)  
**Web** [www.envirosystems.com.au](http://www.envirosystems.com.au)

**DATE** July 2016



## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.