

enviro[®] SurfaPore G



WATER REPELLENT FOR GLASS

PRODUCT DATA SHEET

Enviro SurfaPore G is an alcohol based, liquid formulation that provides water repellency to glass surfaces. Enviro SurfaPore G creates a thin coating with good adhesion that does not change the appearance or transparency of the treated surface. This coating prevents water droplets from “sticking” on glass surfaces and while also preventing salt stains.

FEATURES

- Prevents water and salt stains
- Does not change the appearance of the treated surface
- Easy to apply
- Surface remains transparent

TYPICAL USES

Enviro SurfaPore G is ideal for glass surfaces such as bathroom glass facades, car windshields, windows and more.

APPLICATION SURFACES

Enviro SurfaPore G is designed to be used on glass.

SUBSTRATE PREPARATION

All surfaces should be clean, dry and free from dust, oil, grease, waxes and other foreign material or contamination.

APPLICATION

For any surface, test on a small area before full scale application. The application surface should be dry and clean.

Shake before application. Apply Enviro SurfaPore G using a clean and dry cloth by rubbing the solution onto the surface. Slight cleaning of the surface with a clean cloth after application is recommended for further homogenisation of the film.

Maximum effectiveness is achieved 24 hours post application.

COVERAGE

Estimated coverage of 10-14 m²/L per coat, strongly dependent on the properties of the surface applied.

PACKAGING

Enviro SurfaPore G is supplied in 1L containers.

SHELF LIFE

Enviro SurfaPore G can be stored in its original sealed containers for 18 months, when placed in a cool environment above 4°C. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.

HEALTH & SAFETY ADVICE

Read label before use. Refer to the Safety Data Sheet for full safety and handling procedures.

NOTE: Safety Data Sheets are available under the individual product page on our website or by emailing customerservice@envirosystems.com.au

PHYSICAL PROPERTIES

| Form/Type | Alcohol solution |
|-------------------------|------------------------|
| Colour | Clear |
| Application temperature | From +5°C to 35°C |
| Density | 0.80 g/cm ³ |
| pH | 7.75 ± 0.5 |

We're here to help you!

It is a good idea to keep a journal of your job, whether big or small.

- Take pictures at all stages of your work, including preparation
- Record the quantity and description of products used with corresponding batch numbers
- Record dates and times of when you applied products, from start to finish

Please do not hesitate to contact us for any questions you may have.

Waterproofing Technologies Pty Ltd

Address 295 Princes Highway, St Peters NSW 2044

Phone +61 2 8595 8699

Email customerservice@envirosystems.com.au

Web www.envirosystems.com.au

Date September 2020

Powered by



STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.