

Enviro DeSalin AM

Cleaner, Sanitiser & Mould Prevention



DESCRIPTION

Enviro DeSalin AM is a powerful sanitiser and preservative against microorganisms, mould and algae. It is not only used to clean infected surfaces, but also as a treatment to protect the surface from further mould growth in the future.

Traditional bleach-based mould cleaning solutions usually worsen the problem, as mould spores are resistant to bleach and eventually the cleaning efforts result in contamination of a greater area. Enviro DeSalin AM's formulation effectively kills mould spores and binds on the application surface, offering long-term sterilisation.

FEATURES & BENEFITS

- Multi-purpose – removes and prevents growth of bacteria & mould
- Long-lasting action – only reapply twice a year
- Broad-spectrum – kills mould, mould spores, algae and bacteria
- Easy application
- Water-based – no bleach, no solvents
- Low odour, low VOC

TYPICAL USES

Enviro DeSalin AM can be used to clean and sanitise or for the removal and prevention of mould growth on internal and external surfaces such as:

- Hard surfaces
- External facades and brickwork
- Driveways and pathways
- Bathrooms
- Kitchens
- Basements
- Swimming pools & fountains

APPLICATION SURFACES

Enviro DeSalin AM can be applied to a wide range of surfaces such as:

- Stone
- Tiles
- Painted and unpainted walls
- Masonry
- Cementitious surfaces

PHYSICAL PROPERTIES

Form/Type	Water-based solution
Colour	Clear
Density	0.97 ± 0.05 g/cm ³
Application temperature	From +5°C to +35°C
pH	6.50 ± 0.50

APPLICATION

For any surface, test on a small area before full scale application.

As a cleaner and sanitiser for hard surfaces and floors

Apply DeSalin AM with a spray, brush or cloth, without diluting or diluted with water up to a 1:5 ratio. After application, rinse off the surface with water or a damp cloth to remove any excess of DeSalin AM from the surface.

As a mould cleaner

To sanitise and preserve the surface affected by mould, apply Enviro DeSalin AM by using a brush or spray, without any prior dilution. Allow Enviro DeSalin AM to act on the surface for 24 hours and scrub with a sponge to remove the mould residue. Rinse the surface with water or a wet sponge and allow to dry completely.

Ensure long-term protection from mould by applying Enviro DeSalin AM every six months.

For further information on application or for project specific advice, please consult EnviroSystems.

customerservice@envirosystems.com.au





COVERAGE

Estimated coverage rate of 8-10 m²/L, strongly dependent on the properties of the application surface.

PACKAGING

Enviro DeSalin AM is supplied in 4L bottles.

SHELF LIFE

Enviro DeSalin AM can be stored in its original sealed containers for 24 months, when placed in a cool environment above 4°C. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.

HEALTH & SAFETY ADVICE

Read label before use. Refer to the Safety Data Sheet for full safety and handling procedures.

NOTE: Safety Data Sheets are available under the individual product page on our website or by emailing customerservice@envirosystems.com.au

We're here to help you!

It is a good idea to keep a journal of your project, whether big or small.

- Take pictures at all stages of your work, including preparation.
- Record the quantity and description of products used with corresponding batch numbers.
- Record dates and times of when you applied products, from start to finish.

Please do not hesitate to contact us for any questions you may have.

Waterproofing Technologies Pty Ltd

Address 295 Princes Highway, St Peters NSW 2044
Sydney, Australia
Phone +61 2 8595 8699
Fax +61 2 8595 8660
Email customerservice@envirosystems.com.au
Web www.envirosystems.com.au

DATE December 2019

Powered by  NanoPhos
Pioneering
Nanotechnology



STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.