

# Enviro DeSalin C

## Salt Deposits & Efflorescence Cleaner



### DESCRIPTION

Enviro DeSalin C is a special cleaner based on a concentrated, natural acid. It is an effective formulation for removing residues and salt deposits created due to efflorescence and hard water build-up. Mould and mildew can also be successfully removed. It is ideal for cleaning cementitious surfaces, mortar, grout, stucco, natural and artificial stones.

### FEATURES & BENEFITS

- Cleans salt deposits (efflorescence and hard water build-up)
- Removes mould & mildew
- Environmentally friendly – readily biodegradable formulation
- Easy application

### TYPICAL USES & APPLICATION SURFACES

Enviro DeSalin C can be used for the removal of salt deposits from surfaces such as:

- External facade of buildings
- Natural and artificial stone
- Cementitious surfaces and pavements
- Mortar, grout, stucco
- Roofing, roof tiles and pottery

For continuous protection from salt deposits and mould growth, apply Enviro SurfaPore C after cleaning with Enviro DeSalin C.

### PHYSICAL PROPERTIES

Form/Type	Water-based solution
Colour	Clear
Density	1.07 ± 0.05 g/cm <sup>3</sup>
Application temperature	From +5°C to +35°C
pH	2.30 ± 0.50

### SUBSTRATE PREPARATION

All surfaces should be dry and free from dust, oil, grease and other foreign material or contamination.

For further information on substrate preparation or for project specific advice, please consult EnviroSystems.

[customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

### APPLICATION

For any surface, test on a small area before full scale application.

Rinse the stained surface with Enviro DeSalin C and allow it to act for 2-10 minutes, depending on age, properties and degree of residue build-up. Remove residues by scrubbing with a bristle brush. After removal, wash thoroughly with plenty of water.

Enviro DeSalin C can be used without diluting or up to 1:5 dilution ratio for slightly stained surfaces.

### COVERAGE

Estimated coverage rate of 5-8 m<sup>2</sup>/L, strongly dependent on the properties of the surface applied.

### PACKAGING

Enviro DeSalin C is supplied in 1kg bottles.



## SHELF LIFE

Enviro DeSalin C can be stored in its original sealed containers for 24 months, when placed in a cool environment above 4°C. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.

## HEALTH & SAFETY ADVICE

Read label before use. Refer to the Safety Data Sheet for full safety and handling procedures.

**NOTE:** Safety Data Sheets are available under the individual product page on our website or by emailing [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)

## We're here to help you!

It is a good idea to keep a journal of your project, whether big or small.

- Take pictures at all stages of your work, including preparation.
- Record the quantity and description of products used with corresponding batch numbers.
- Record dates and times of when you applied products, from start to finish.

Please do not hesitate to contact us for any questions you may have.

Waterproofing Technologies Pty Ltd

**Address** 295 Princes Highway, St Peters NSW 2044  
Sydney, Australia  
**Phone** +61 2 8595 8699  
**Fax** +61 2 8595 8660  
**Email** [customerservice@envirosystems.com.au](mailto:customerservice@envirosystems.com.au)  
**Web** [www.envirosystems.com.au](http://www.envirosystems.com.au)

**DATE** December 2019

Powered by  NanoPhos  
Pioneering  
Nanotechnology



## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by EnviroSystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not EnviroSystems Technologies are responsible for carrying out procedures appropriate to a specific application.