

Enviro DeSalin DG

Heavy-Duty Degreaser



DESCRIPTION

Enviro DeSalin DG is a professional grade, heavy-duty degreaser. It easily cuts through, emulsifies and removes oil, grease, grime, fuel and sludge. Ideal for sensitive surfaces, as it generates no acid or acidic by-products.

Enviro DeSalin DG is recommended for professional use but can also be used for Do-It-Yourself (DIY) applications.

FEATURES & BENEFITS

- Heavy-duty
- Evaporates fast – minimises downtime
- Does not produce acidic by-products – good for sensitive surfaces
- Environmentally friendly – biodegradable, water-based and no ozone depleting chemicals
- Non-flammable – reduced risk of fire due to incidental contact with live equipment
- Easy application

TYPICAL USES

Enviro DeSalin DG is ideal for emulsification of oil, fuel residues, grease, grime, sludge and wherever there are oily stains.

PHYSICAL PROPERTIES

Form/Type Water-based solution

Colour Clear/yellowish

Application temperature From +5°C to +35°C

pH 13.50 ± 0.50

APPLICATION

For any surface, test on a small area before full scale application.

Spray liberally and allow running off. Use extension tube for hard-to-reach areas. Allow equipment to fully dry and vent before using. Wiping with a dry, absorbent cloth can accelerate drying time.

Do not use on plastics such as acrylic, ABS and polycarbonate. If uncertain, test on a small area before using. Not for use on sensitive electronics. For personal safety, do not use while equipment is in use.

For further information on application or for project specific advice, please consult EnviroSystems.

customerservice@envirosystems.com.au

COVERAGE

Estimated coverage rate of 4-6 m²/L, strongly dependent on the properties of the surface applied.

PACKAGING

Enviro DeSalin DG is supplied in 4L bottles.

SHELF LIFE

Enviro DeSalin DG can be stored in its original sealed containers for 30 months, when placed in a cool environment above 4°C. Once opened and resealed for later use, the shelf life could vary depending on storage conditions. Always check product quality before using after prolonged periods of storage. If unsure, please contact EnviroSystems for advice.



HEALTH & SAFETY ADVICE

Read label before use. Refer to the Safety Data Sheet for full safety and handling procedures.

NOTE: Safety Data Sheets are available under the individual product page on our website or by emailing customerservice@envirosystems.com.au

We're here to help you!

It is a good idea to keep a journal of your project, whether big or small.

- Take pictures at all stages of your work, including preparation.
- Record the quantity and description of products used with corresponding batch numbers.
- Record dates and times of when you applied products, from start to finish.

Please do not hesitate to contact us for any questions you may have.

Waterproofing Technologies Pty Ltd

Address 295 Princes Highway, St Peters NSW 2044
Sydney, Australia
Phone +61 2 8595 8699
Fax +61 2 8595 8660
Email customerservice@envirosystems.com.au
Web www.envirosystems.com.au

DATE December 2019

Powered by 



STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Envirosystems Technologies either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Envirosystems Technologies are responsible for carrying out procedures appropriate to a specific application.