

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B

Version: 3  
 Issued by: Envirosystems  
 Date of Issue: April 2026

Hazard Identifiers



## SECTION 1 – IDENTIFICATION OF MATERIAL & SUPPLIER

- 1.1 Product Name:** Enviro HP1200  
**Manufacturer's Product Code:** N/A
- 1.2 Recommended Use:** 2 Pack Polyurethane
- 1.3 Company:** Envirosystems  
**Address:** 295 Princes Highway St Peters, NSW 2044  
**Website:** www.envirosystems.com.au  
**Telephone:** +61 2 85958699 (business hours)  
**Fax:** +61 2 85958660
- 1.4 Emergency Telephone:** Poisons Centre – 131126
- Other Information:** All information in this SDS is to the best of our knowledge at time of publication. Users of this product should fully review this SDS prior to use to ensure best safety practices. Further information and or clarification can be obtained by contacting our technical department on the above telephone number.

## SECTION 2 – HAZARDS IDENTIFICATION

- 2.1 Hazard Classification:** Classified as **Hazardous** according to WHS Regulations, Australian GHS criteria and a **Non-Dangerous Goods** according to the Australian Dangerous Goods Code.

Class	Category
Eye Irritation	2a
Specific target organ toxicity - repeated exposure	2
Hazardous to the aquatic environment- acute	2
Hazardous to the aquatic environment- chronic	2

- 2.2 Label Elements**



Signal word

Warning

H-code	Hazard Statements
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H412	Harmful to aquatic life with long lasting effects.
P-Code	Precautionary Statement - Prevention
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



P233	Keep container tightly closed.
P260	Do not breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
<b>P-Code</b>	<b>Precautionary Statement - Response</b>
P301, P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302, P352	IF ON SKIN: Wash with soap and water.
P303, P361, P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304, P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305, P351, P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P308, P313	IF exposed or concerned: Get medical advice/attention.
P314	Get Medical advice/attention if you feel unwell.
P321	Specific treatment (see first aid measures on this safety data sheet).
P331	Do NOT induce vomiting.
P332, P313	If skin irritation occurs: Get medical advice/attention.
P337, P313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370, P378	In case of fire: see fire-fighting measures on this safety data sheet.
P391	Collect spillage.
<b>P-Code</b>	<b>Precautionary Statement - Storage</b>
P405, P303, P235	Store locked up in a cool well-ventilated area
P407	Maintain air gap between stacks/pallets.
P420	Store away from other materials.
<b>P-Code</b>	<b>Precautionary Statement - Disposal</b>
P501	Dispose of contents / containers to hazardous or special waste collection point. In accordance with local regulation

### 2.3 Other Hazards

None known

## SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

See section below for Mixtures

### 3.2 Mixtures

CAS No.	Material	Content %
68479-98-1	diethyltoluenediamine	10-30
	Ingredients determined to be Non-Hazardous	Balance

## SECTION 4 – FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General Advice:

Immediately remove contaminated clothing. If in danger of loss of consciousness,

place patient in recovery position and transport accordingly. Apply artificial respiration if necessary. First aid personnel should pay attention to the own safety.

**Ingestion:**

Do not induce vomiting. Observe the patient carefully. Wash mouth with water. Never give liquid to a person showing signs of being sleepy or with reduced awareness. Immediately call a poison center or doctor/physician and get medical attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

**Inhalation:**

Move to an area free from further exposure. Seek medical attention. Keep patient calm and remove to fresh air. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Call a poison center or doctor/physician if you feel unwell.

**Eye Contact:**

While holding eyes open, gently flood with plenty of fresh water for 15 minutes. Seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.

**Skin Contact:**

Flush contacted area thoroughly with soap and plenty of water, shower if available. Seek medical attention if irritation occurs. Remove contaminated clothing including footwear. If skin irritation occurs: Get medical advice/attention. In case of burns: Immerse in cool water/wrap in wet bandages.

- |  |   |
|--|---|
| <b>4.2 Most important symptoms and effects, both acute and delayed</b> | Notify medical personnel of contaminated situations and have them take appropriate protective measures. If exposed or concerned, get medical attention/advice. Any relevant information can be found in other parts of this section and in sections 2 and 11. |
| <b>4.3 Advice for doctor</b>   | Treat symptomatically. May cause an allergic skin reaction. It causes serious eye damage.   |

## SECTION 5 – FIRE FIGHTING MEASURES

- |  |   |
|--|---|
| <b>5.1 Extinguishing media</b>                                   | Suitable extinguishing media:<br>Dry chemical powder, foam, BCF (where regulations permit) and alcohols stable foams. Water fog or fine spray for large fires only.   |
| <b>5.2 Special hazards arising from the substance or mixture</b> | Avoid contamination with epoxy resins, isocyanates.   |
| <b>5.3 Advice for firefighters</b>                               | Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO <sub>2</sub> ), phenolics products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. Vapor or gas is burned at distant ignition sources can be spread quickly. The extremely low flash point made by fire-fighters may be less effective at digesting weeks. |

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



- 6.1 Personal precautions, protective equipment and emergency procedures** Secure the area, isolate hazard area and deny entry. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material. Do not direct water at spill or source of leak. Avoid skin contact and inhalation. Cleanup and disposal under expert supervision is advised. Keep unauthorized people away.
- 6.2 Environmental precautions** Do not discharge into sewers or waterways and soil. If large amounts have been spilled, inform the relevant authorities.
- 6.3 Methods and material for containment and cleaning up** Small spills should be absorbed with dry, inert filler (soil or sand) which then can be shoveled into appropriately labeled drums for disposal. Disposal of this material should be undertaken by a registered chemical disposal company. Wear breathing respirator plus protective gloves.
- 6.4 Reference to other sections** Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

## SECTION 7 – HANDLING & STORAGE

- 7.1 Precautions for safe handling** Ensure thorough ventilation of stores and work areas. Handle in accordance with good industrial hygiene and safety practice. When using do NOT eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Protection against fire and explosion: The product is combustible. Prevent electrostatic charge - sources of ignition should be kept well clear – fire extinguishers should be kept handy. Avoid all personal contact, including inhalation. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Do NOT allow clothing with this material to stay in contact with skin. Should be stored under cover, out of direct sunlight, protected from rain, protected from physical damage and well away from moisture, acids and alkalis. Do NOT enter confined spaces until atmosphere has been checked.
- 7.2 Conditions for safe storage**  
**Storage Requirements:**  
Store in a cool, dry area away from incompatible materials.  
**Incompatible materials:**  
Avoid reaction with epoxy resins, isocyanates.  
**Temperature Conditions:**  
Up to 40° C  
**Protection from weather:**  
Store undercover and away from frost and moisture. Avoid reaction with epoxy resins, isocyanates
- 7.3 Specific end use(s)** Once applied, produces a polyurethane coating.
- 7.4 Regulations and standards (Australia):** Classified as Hazardous Liquid which should be stored and handled in accordance with regulations

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**

Exposure limits:

Ingredient	TWA	STEL
None known		

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



Emergency limits:

Ingredient	TEEL-1	TEEL-2	TEEL-3
None known			

### 8.2 Exposure controls

#### General protection and hygiene measures:

Avoid exposure. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not eat, drink or smoke when handling. Wash hands at the end of work and before eating. Keep working clothes separately. Remove contaminated, soaked clothing immediately. Clean work areas regularly.

1st monitor air quality should be checked regularly in accordance with AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment (AS/NZS 1715). Then use dilution ventilation systems to dilute and displace contaminated air with fresh air supplied to the work area by mechanical exhaust fans (make sure explosion and spark proof equipment as solvents are used) or natural air currents through doors, windows or other openings in the building.

#### Personal protection equipment:

##### *Respiratory protection*

Avoid breathing of vapors/gases. When engineering controls are not effective in controlling airborne exposure then respiratory equipment should be used to protect against airborne contaminant. The appropriate respiratory equipment can be determined based upon actual airborne concentration and can vary depending on individual circumstances. Select and use respirators in accordance with AS/NZS 1715/1716.

##### *Eye protection*

Safety glasses with side shields or chemical goggles. Full face shield may be required for supplementary but never for primary protection of eyes. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

##### *Hand protection*

Suitable materials for safety gloves; Laminated and Nitrile rubber  $\geq 0.35\text{mm}$ , contaminated gloves should be disposed of.

##### *Skin protection*

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. For small amounts a long sleeve shirt and full length pants should be sufficient. Take care to make sure no static build up occurs.

### 8.3 Further information for system design and engineering measures

Ventilation is recommended under normal use conditions. State regulations on speed and direction of airflow away from operators must be observed. Keep containers closed when not in use.

## SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

9.1	<b>Odour:</b>	Slightly
	<b>Odour Threshold</b>	No test data available
	<b>Colour:</b>	Green or Grey
	<b>Physical State:</b>	Smooth flowing liquid
	<b>Flash Point:</b>	$>94^{\circ}\text{C}$

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



<b>Boiling Point:</b>	>100°C
<b>Melting Point:</b>	Not Available
<b>Specific Gravity:</b>	1.0±0.2 (@25°C)
<b>Viscosity:</b>	Not Available
<b>pH (5% solution):</b>	Not Available
<b>Solubility in Water (g/L):</b>	Insoluble
<b>Flammability:</b>	N/A
<b>Explosive Lower Limit:</b>	N/A
<b>Explosive Higher Limit:</b>	N/A
<b>Vapour Pressure:</b>	N/A
<b>Vapour Density (Air = 1)</b>	Heavier than air
<b>Volatile component</b>	Not Available
<b>Auto-ignition temperature (°C)</b>	N/A
<b>Partition coefficient of n-octanol/water:</b>	N/A
<b>Decomposition temperature:</b>	N/A
<b>Molecular weight:</b>	N/A
<b>9.2 Other information</b>	None available

## SECTION 10 – STABILITY AND REACTIVITY

<b>10.1 Reactivity; Chemical stability;</b>	If stored and handled in accordance with standard industrial practices not hazardous reactions are known. Unstable in the present of incompatible material. May vent and release flammable gas at high temperature. May explode when exposed to high temperature or heated.
<b>-3 Possibility of hazardous reactions</b>	
<b>10.4 Conditions to avoid</b>	Avoid contact with incompatible materials and condition. Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.
<b>10.5 Incompatible materials</b>	Flammable materials. Reducing agents, Water
<b>10.6 Hazardous decomposition products</b>	May emit flammable vapour, fume, hazardous gas if involved in fire.

## SECTION 11 – TOXICOLOGICAL INFORMATION

<b>Acute Toxicity/Effects</b>	Oral Diethyltoluenediamine LD50 (Rat, male and female): 738 mg/kg Method: OECD Test Guideline 401
	Dermal diethyltoluenediamine LD50 (Rat, male and female): > 2,000 mg/kg: OECD Test Guideline 401
	Inhalation No data available
	Skin corrosion/irritation Diethyltoluenediamine Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation
	Serious eye damage/irritation: Diethyltoluenediamine Species: Rabbit Result: Irritating to eyes.
	Respiratory sensitization: No data available

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



Skin sensitization:  
Diethyltoluenediamine Test Type : Maximization Test Species: Guinea pig Result:  
Did not cause sensitization on laboratory animals

### Chronic Toxicity/Effects

Carcinogenicity: IARC  
Diethyltoluenediamine Not classified due to data which are conclusive although insufficient for classification.

Germ cell mutagenicity:  
diethyltoluenediamine Results: ambiguous

Reproductive toxicity:  
Diethyltoluenediamine Remarks: study scientifically unjustified

Developmental Toxicity/Teratogenicity:  
No data available

STOT-single exposure:  
No Data Available

STOT-repeated exposure:  
Diethyltoluenediamine, May cause damage to organs through prolonged or repeated Exposure, Pancreas

Aspiration hazard:  
No data available

### Long Term Effects:

No data available.

## SECTION 12 – ECOLOGICAL INFORMATION

### Toxicity

Fish:  
Diethyltoluenediamine LC50 (Pimephales promelas (fathead minnow)): > 106 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203

Crustaceans:  
Diethyltoluenediamine EC50 (Daphnia magna (Water flea)): 0.5 mg/l  
End point: Immobilization Exposure time: 48 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 202

Algae:  
Diethyltoluenediamine EC10 (Desmodesmus subspicatus (green algae)): ca. 54 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201

### Microorganisms/Effect on sludge

Diethyltoluenediamine EC10 (Pseudomonas putida): 170 mg/l  
End point: Growth rate Exposure time: 24 h Test Type: static test Analytical monitoring: no Method: According to a standard method

### Persistence and degradability

Diethyltoluenediamine  
Biodegradability : Result: Not biodegradable. Method: QSAR  
Stability in water : Remarks: Not susceptible to hydrolysis.

Dibutyltin dilaurate  
Biodegradability anaerobic - Exposure time 39 d

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



Result: 23 % - Not readily biodegradable.  
(OECD Test Guideline 301F)

<b>Bioaccumulative potential</b>	Diethyltoluenediamine Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4). Partition coefficient: noctanol/water : log Pow: 1.38 (77 °F / 25 °C) Method: OECD Test Guideline 107
<b>Biodegration:</b>	No data aviable
<b>Mobility in soil</b>	Diethyltoluenediamine Distribution among environmental compartments : Medium: Soil log Koc: ca. 2.2 Method: QSAR Remarks: Will be likely mobile in the environment
<b>Additional Information</b>	Do NOT discharge into sewer or waterways

## SECTION 13 – DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

#### Material Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration. Do **NOT** allow wash water from cleaning or process equipment to enter drains.

#### Uncleaned packaging Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

## SECTION 14 – TRANSPORT INFORMATION

### Transport Information

Is classified Dangerous Good according to the Australian Code for the Transportation of Dangerous Goods by Road and Rail.

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;  
(c) packaging's that do not incorporate a receptacle exceeding 500 Kg (L);  
or  
(d) IBCs.

U.N. Number:	N/A
DG Class:	N/A
Subsidiary class	N/A
EPG card:	N/A
Hazchem Code:	N/A
Proper Shipping Name:	Environmentally hazardous substance liquid N.O.S
Packing Group:	N/A
Poison Schedule	N/A

### Classification for SEA transport (IMO-IMDG)

U.N. Number:	3082
DG Class:	9

# SAFETY DATA SHEETS (SDS)

## Enviro HP1200 Part B



	Subsidiary class	N/A
	Proper Shipping Name:	Environmentally hazardous substance liquid N.O.S
	Packing Group:	III
	Marine Pollutant:	Yes
<b>Classification for AIR transport (IATA/ICAO)</b>	U.N. Number:	3082
	DG Class:	9
	Subsidiary class	N/A
	Proper Shipping Name:	Environmentally hazardous substance liquid N.O.S
	Packing Group:	III

Label



### SECTION 15 – REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

National and local regulations must be observed. For information on labeling please refer to section 2 of this document.

**Poisons Schedule Number: S5**

**Australian Inventory:  
Controlled Schedule  
Carcinogenic Substances:**

Listed  
Not listed substances

### SECTION 16 – OTHER INFORMATION

Safety Data Sheets are updated regularly. Please ensure you have a current copy. SDS can be obtained from our website: [www.envirosystems.com.au](http://www.envirosystems.com.au)

The SDS should be used to assist in the Risk Management. Many other factors determine whether the reported Hazards are risks in any given workplace.

Specific Risks may be determined by reference to various Exposure Scenarios, Scale of use, Frequency of use and current or available engineering controls must be considered.

This document belongs entirely to Enviro Systems Pty Ltd and apart of the use of it for the purposes of private study, research, review or criticism, no part may be reproduced or re-used without prior permission from ENVIROSYSTEMS.

Emergency Telephone: Poisons Centre – 131 126