

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



Hazard Identifiers

Version: 2

Issued by: Envirosystems

Date of Issue: September 2026



SECTION 1 – IDENTIFICATION OF MATERIAL & SUPPLIER

- 1.1 Product Name:** Enviro HP1200 AC Part B
Manufacturer's Product Code: N/A
- 1.2 Recommended Use:** Component of a polyurethane system
- 1.3 Company:** Envirosystems
Address: 295 Princes Highway St Peters, NSW 2044.±
Website: www.envirosystems.com.au
Telephone: +61 2 85958699 (business hours)
Fax: +61 2 85958660
- 1.4 Emergency Telephone:** Poisons Centre – 131126
- Other Information:** All information in this SDS is to the best of our knowledge at time of publication. Users of this product should fully review this SDS prior to use to ensure best safety practices. Further information and or clarification can be obtained by contacting our technical department on the above telephone number.

SECTION 2 – HAZARDS IDENTIFICATION

- 2.1 Hazard Classification:** Classified as **Hazardous** according to WHS Regulations, Australian GHS criteria and a **Dangerous Goods** according to the Australian Dangerous Goods Code.

Class	Category
Acute toxicity - Oral	4
Skin corrosion/irritation	1
Eye Irritation	1
Skin sensitization	1
Hazardous to the aquatic environment- chronic	3

- 2.2 Label Elements**



Signal word

Danger

H-code	Hazard Statements
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
P-Code	Precautionary Statement - Prevention
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



	and understood.
P233	Keep container tightly closed.
P260	Do not breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P-Code	Precautionary Statement - Response
P301, P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303, P361, P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304, P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305, P351, P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P308, P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P314	Get Medical advice/attention if you feel unwell.
P321	Specific treatment (see first aid measures on this safety data sheet).
P331	Do NOT induce vomiting.
P332, P313	If skin irritation occurs: Get medical advice/attention.
P337, P313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370, P378	In case of fire: see fire-fighting measures on this safety data sheet.
P391	Collect spillage.
P-Code	Precautionary Statement - Storage
P405, P303, P235	Store locked up in a cool well-ventilated area
P407	Maintain air gap between stacks/pallets.
P420	Store away from other materials.
P-Code	Precautionary Statement - Disposal
P501	Dispose of contents / containers to hazardous or special waste collection point. In accordance with local regulation

2.3 Other Hazards

None known

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

3.2 Mixtures

See section below for Mixtures

CAS No.	Material	Content %
9046-10-0	Polyoxypropylenediamine	30-60
64852-22-8	Glyceryl poly(oxypropylene)triamine	< 5
	Ingredients determined to be Non-Hazardous	Balance

SECTION 4 – FIRST AID MEASURES

4.1 Description of first aid measures

General Advice:

Immediately remove contaminated clothing. If in danger of loss of consciousness, place patient in recovery position and transport accordingly. Apply artificial respiration if necessary. First aid personnel should pay attention to the own safety.

Ingestion:

Do not induce vomiting. Observe the patient carefully. Wash mouth with water. Never give liquid to a person showing signs of being sleepy or with reduced awareness. Immediately call a poison center or doctor/physician and get medical attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Inhalation:

Move to an area free from further exposure. Seek medical attention. Keep patient calm and remove to fresh air. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Call a poison center or doctor/physician if you feel unwell.

Eye Contact:

While holding eyes open, gently flood with plenty of fresh water for 15 minutes. Seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.

Skin Contact:

Flush contacted area thoroughly with soap and plenty of water, shower if available. Seek medical attention if irritation occurs. Remove contaminated clothing including footwear. If skin irritation occurs: Get medical advice/attention. In case of burns: Immerse in cool water/wrap in wet bandages. Take off contaminated clothing and wash before reuse.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. It causes serious skin and eye damage.

Notify medical personnel of contaminated situations and have them take appropriate protective measures. If exposed or concerned, get medical attention/advice. Any relevant information can be found in other parts of this section and in sections 2 and 11.

4.3 Advice for doctor

Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:

Dry chemical powder, foam, BCF (where regulations permit) and alcohols stable foams.

Water fog or fine spray for large fires only.

5.2 Special hazards arising from the substance or mixture

Avoid contamination with epoxy resins, isocyanates.

5.3 Advice for firefighters

Hazchem code 2X. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO₂), phenolics products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. Vapor or gas is burned at distant ignition sources can be spread quickly. The extremely low flash point made by fire-fighters may be less effective at digesting weeks.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- | | |
|--|--|
| 6.1 Personal precautions, protective equipment and emergency procedures | Secure the area, isolate hazard area and deny entry. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material. Do not direct water at spill or source of leak. Avoid skin contact and inhalation. Cleanup and disposal under expert supervision is advised. Keep unauthorized people away. |
| 6.2 Environmental precautions | Do not discharge into sewers or waterways and soil. If large amounts have been spilled, inform the relevant authorities. |
| 6.3 Methods and material for containment and cleaning up | Small spills should be absorbed with dry, inert filler (soil or sand) which then can be shoveled into appropriately labeled drums for disposal. Disposal of this material should be undertaken by a registered chemical disposal company. Wear breathing respirator plus protective gloves. |
| 6.4 Reference to other sections | Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13). |

SECTION 7 – HANDLING & STORAGE

- | | |
|--|---|
| 7.1 Precautions for safe handling | Ensure thorough ventilation of stores and work areas. Handle in accordance with good industrial hygiene and safety practice. When using do NOT eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Protection against fire and explosion: The product is combustible. Prevent electrostatic charge - sources of ignition should be kept well clear – fire extinguishers should be kept handy. Avoid all personal contact, including inhalation. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Do NOT allow clothing with this material to stay in contact with skin. Should be stored under cover, out of direct sunlight, protected from rain, protected from physical damage and well away from moisture, acids and alkalis. Do NOT enter confined spaces until atmosphere has been checked. |
| 7.2 Conditions for safe storage | Storage Requirements:
Store in a cool, dry area away from incompatible materials.
Incompatible materials:
Avoid reaction with epoxy resins, isocyanates. Acids. Corrosive to copper, zinc, and many metal surfaces.
Temperature Conditions:
Up to 40° C
Protection from weather:
Store undercover and away from frost and moisture. Avoid reaction with epoxy resins, isocyanates |
| 7.3 Specific end use(s) | Once applied, produces a polyurethane coating. |

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



7.4 Regulations and standards (Australia):

Classified as Hazardous Liquid which should be stored and handled in accordance with regulations

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limits:

Ingredient	TWA	STEL
None known		

Emergency limits:

Ingredient	TEEL-1	TEEL-2	TEEL-3
None known			

8.2 Exposure controls

General protection and hygiene measures:

Avoid exposure. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not eat, drink or smoke when handling. Wash hands at the end of work and before eating. Keep working clothes separately. Remove contaminated, soaked clothing immediately. Clean work areas regularly.

1st monitor air quality should be checked regularly in accordance with AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment (AS/NZS 1715). Then use dilution ventilation systems to dilute and displace contaminated air with fresh air supplied to the work area by mechanical exhaust fans (make sure explosion and spark proof equipment as solvents are used) or natural air currents through doors, windows or other openings in the building.

Personal protection equipment:

Respiratory protection

Avoid breathing of vapors/gases. When engineering controls are not effective in controlling airborne exposure then respiratory equipment should be used to protect against airborne contaminant. The appropriate respiratory equipment can be determined based upon actual airborne concentration and can vary depending on individual circumstances. Select and use respirators in accordance with AS/NZS 1715/1716.

Eye protection

Safety glasses with side shields or chemical goggles. Full face shield may be required for supplementary but never for primary protection of eyes. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Hand protection

Suitable materials for safety gloves; Laminated and Nitrile rubber $\geq 0.35\text{mm}$, contaminated gloves should be disposed of.

Skin protection

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. For small amounts a long sleeve shirt and full length pants should be sufficient. Take care to make sure no static build up occurs.

8.3 Further information for system

Ventilation is recommended under normal use conditions. State regulations on

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



design and engineering measures

speed and direction of airflow away from operators must be observed. Keep containers closed when not in use.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

9.1	Odour:	Amine like
	Odour Threshold	No test data available
	Colour:	Various
	Physical State:	Flowing liquid
	Flash Point:	Not Available
	Boiling Point:	Not Available
	Melting Point:	Not Available
	Specific Gravity:	1.2±0.2 (@25°C)
	Viscosity:	600 - 1000 mPa s
	pH (5% solution):	Not Available
	Solubility in Water (g/L):	Not Available
	Flammability:	Not Available
	Explosive Lower Limit:	Not Available
	Explosive Higher Limit:	Not Available
	Vapour Pressure:	Not Available
	Vapour Density (Air = 1)	Not Available
	Volatile component	Not Available
	Auto-ignition temperature (°C)	Not Available
	Partition coefficient of n-octanol/water:	Not Available
	Decomposition temperature:	Not Available
	Molecular weight:	Not Available
9.2	Other information	None available

SECTION 10 – STABILITY AND REACTIVITY

10.1	Reactivity; Chemical stability;	If stored and handled in accordance with standard industrial practices not hazardous reactions are known. Unstable in the present of incompatible material. May vent and release flammable gas at high temperature. May explode when exposed to high temperature or heated.
-3	Possibility of hazardous reactions	
10.4	Conditions to avoid	Avoid contact with incompatible materials and condition. Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.
10.5	Incompatible materials	Acids. Corrosive to copper, zinc, and many metal surfaces.
10.6	Hazardous decomposition products	May emit flammable vapour, fume, hazardous gas if involved in fire.

SECTION 11 – TOXICOLOGICAL INFORMATION

Acute Toxicity/Effects

Oral
Polyoxypropylenediamine = 242 mg/kg (Rat) (From manufacture SDS)

Dermal
Polyoxypropylenediamine = 360 mg/kg (Rabbit) From manufacture SDS)

Inhalation
No data available

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



Skin corrosion/irritation
Causes skin irritation. Causes burns.

Serious eye damage/irritation:
Causes serious eye irritation. Causes burns.

Respiratory sensitization:
No data available

Skin sensitization:
May cause an allergic skin reaction.

Chronic Toxicity/Effects

Germ cell mutagenicity:
No information available.

Carcinogenicity:
No information available.

Reproductive toxicity:
No information available.

STOT - single exposure:
No information available.

STOT - repeated exposure:
No information available.

Aspiration hazard:
No information available.

Long Term Effects:

No data available.

SECTION 12 – ECOLOGICAL INFORMATION

Toxicity	Harmful to aquatic life with long lasting effects. Keep out of waterways.
Microorganisms/Effect on sludge	No information available.
Persistence and degradability	No information available.
Bioaccumulative potential	No information available.
Biodegradation:	No information available.
Mobility in soil	No information available.
Additional Information	Do NOT discharge into sewer or waterways

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Material Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility.

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration. Do **NOT** allow wash water from cleaning or process equipment to enter drains.

Uncleaned packaging Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14 – TRANSPORT INFORMATION

Transport Information

Is classified as a Dangerous Good according to the Australian Code for the Transportation of Dangerous Goods by Road and Rail.

U.N. Number: 2735
DG Class: 8
Subsidiary class: N/A
EPG card: N/A
Hazchem Code: 2X
Proper Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS O,O'-BIS(2-AMINOPROPYL)PROPYLENE GLYCOL)
Packing Group: III
Poison Schedule: 5

Classification for SEA transport (IMO-IMDG)

U.N. Number: 2735
DG Class: 8
Subsidiary class: N/A
Proper Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS O,O'-BIS(2-AMINOPROPYL)PROPYLENE GLYCOL)
Packing Group: III
IMDG EMS Fire: F-A
IMDG EMS Spill: S-B
Marine Pollutant: YES

Classification for AIR transport (IATA/ICAO)

U.N. Number: 2735
DG Class: 8
Subsidiary class: N/A
Proper Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS O,O'-BIS(2-AMINOPROPYL)PROPYLENE GLYCOL)
Packing Group: III

Label

Corrosive DG 8

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific

National and local regulations must be observed. For information on labeling please refer to section 2 of this document.

SAFETY DATA SHEETS (SDS)

Enviro HP1200 AC Part B



for the substance or mixture

Poisons Schedule Number: 5

Australian Inventory:

Listed

Controlled Schedule

Not listed substances

Carcinogenic Substances:

SECTION 16 – OTHER INFORMATION

Safety Data Sheets are updated regularly. Please ensure you have a current copy. SDS can be obtained from our website: www.envirosystems.com.au

The SDS should be used to assist in the Risk Management. Many other factors determine whether the reported Hazards are risks in any given workplace.

Specific Risks may be determined by reference to various Exposure Scenarios, Scale of use, Frequency of use and current or available engineering controls must be considered.

This document belongs entirely to Enviro Systems Pty Ltd and apart of the use of it for the purposes of private study, research, review or criticism, no part may be reproduced or re-used without prior permission from ENVIROSYSTEMS.

Emergency Telephone: Poisons Centre – 131 126