

Enviro Mortar Additive

A High Solids Latex Additive that Fortifies Mortars, Renders, and Screeds



DESCRIPTION

Enviro Mortar Additive is an acrylic polymer additive formulated for use with cement-based mortars, renders and adhesives to increase strength and flexibility. It can be blended with sand and cement to improve strength and flexibility or mixed with neat cement to produce a bonding slurry coat.

FEATURES & BENEFITS

- High polymer content for increased adhesion
- Compatible with a wide range of cement-based mortars, renders, and adhesives
- Increases mortar and screed strength and flexibility.
- Low VOC content

PRODUCT INFORMATION

Packaging	4L Jerry Cans and 20L Cubes
Shelf Life	12 months from the date of manufacture if stored as per storage recommendations
Storage Conditions	Must be stored in a cool, dry environment above ground level
Compatible Adhesives	Enviro Mastic Enviro Mastic Plus
Compatible Membranes	Enviro Hydrostatic 1
Compatible Mortars & Screeds	Enviro Mortar 45 Enviro Rapid Screed Enviro Plug

COVERAGE RATE

For coverage rates specific to your project, contact EnviroSystems technical support.

MIXING

Shake or stir well before use.

APPLICATION

Mortars & renders: Mix one part Enviro Mortar Additive to three parts water and use as the gauging liquid.

Slurry coat: Mix one part neat cement with one part Enviro Mortar Additive.

For applications or situations not covered above, contact EnviroSystems technical support.

CLEANING

Tools and equipment can be cleaned with water while the additive is still wet.

LIMITATIONS

Do not use Enviro Mortar Additive in temperatures below 5°C or above 38°C.

HEALTH & SAFETY ADVICE

Enviro Mortar Additive is a non-hazardous product. Ensure adequate ventilation during use. If the product splashes into eyes, rinse thoroughly with clean water for at least 15 minutes. If it contacts the skin, wash well to remove.

KEEP OUT OF REACH OF CHILDREN

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to accuracy, reliability, or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

NOTE: Field service where provided does not constitute supervisory responsibility. Suggestions made by EnviroSystems, either verbally or in writing may be followed, modified, or rejected by the owner, engineer, or contractor since they, and not EnviroSystems, are responsible for carrying out procedures appropriate to a specific project.

NOTE: All products manufactured by EnviroSystems comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.



ADHESIVES

Enviro Mortar Additive

A High Solids Latex Additive that Fortifies Mortars,
Renders, and Screeds



CONTACT ENVIROSYSTEMS

General Enquiries

info@envirosystems.com.au | 1300 WATERPROOF (1300 928 377)

New South Wales – Head Office

Ground Floor, 295 Princes Hwy, St Peters NSW 2044 |
nswsales@envirosystems.com.au

Queensland

Unit 3, 28 Burnside Rd, Yatala QLD 4207 | qldsales@envirosystems.com.au

Victoria

49 Wood St, Thomastown VIC 3074 |
vicsales@envirosystems.com.au

Western Australia

78 Discovery Dr, Bibra Lake WA 6163 |
wasales@envirosystems.com.au

